

Stone | EDGE

SURFACES

Professional Grade Concrete Overlays



Commonly Sold With
Fiberglass Mat

DECK RESIN

applications

DESCRIPTION

Stone Edge Surfaces Deck Resin is a water-based, high strength yet pliable, general purpose latex binder styrene-butadiene emulsion polymer of medium to high stiffness. Deck Resin is a mid barrier waterproofing layer in the Stone Edge Surfaces Deck & Balcony Waterproofing System, and can also be used in showers and other areas to create a waterproofing layer over the walls and floors before applying the overlay materials. **Deck Resin**, when combined with fiberglass mat adds strength and body, by saturating and soaking through to adhere to the substrate. When dry, it forms a flexible, tough waterproofing layer that becomes the substrate for the next layer in the waterproofing system.

MOST COMMON USES

- Deck & Balcony Waterproofing System Mid-Barrier Waterproofing Layer.
- Behind the walls of Showers or high water use areas and under shower pans.
- Over scratch coat or behind the pool plaster in Swimming Pools.
- For Commercial or Residential Indoor or Outdoor use as an underlayment only...as Deck Resin is NOT UV stable.

APPLICATION

BASE/TOP COAT: Base Coat, Water Based Mid-Barrier Waterproofing layer that is applied in unison with fiberglass mat or other similar materials or mesh.

APPLICATION METHOD: Roller or paint brush

WORKING TIME: Dry to the Touch 1-2 hours

PRODUCTS USED WITH OR APPLIED OVER:

- Stone Edge Surfaces Deck & Balcony Waterproofing System
 - Pro Bond
 - Smooth Coat
 - Spray Mix
 - Fiberglass Mat
 - Fiber lath or Mesh
 - Nylon Mesh or Mat
- COVERAGE:** 100-200 SQFT Per Gallon



For additional installation examples, images and training Videos, visit us online, call or email:

www.stoneedgesurfaces.com | 844-786-6333

info@stoneedgesurfaces.com

Stone Edge Surfaces Division - Turley International Resources, LLC 4322 South 80th Street, Mesa, AZ 85212