

PRODUCT AND COMPANY IDENTIFICATION	
PRODUCT MANUFACTURER: Stone Edge Surfaces	MANUFACTURER: Turley International Resources, LLC.
PRODUCT NAME: Deck Seal Tint Pack Color	4322 South 80 th Street
14 Tint Pack Colors are: Bone, Adobe, Taupe, Cream, Buff, Latte, Mist Gray, Dove Gray, Storm Gray, Cappuccino, Pecan, Toffee, Salmon, Terracotta	Mesa, AZ 85212 - USA
	TEL: 844-786-6333 E: info@stoneedgesurfaces.com
EMERGENCY: Dial 911 or go to Emergency Room Immediately	MEDICAL: Dial 911 or go to Emergency Room Immediately
PRODUCT COMPOSITION	
Stone Edge Surfaces Deck Seal Tint Pack Colors are 8oz bottles of concentrated natural iron oxide pigments, water and other additives that make them easy to pour and mix with our 5 gallon buckets of Deck Seal deep base waterproofing sealer to create 14 beautiful deck colors. (See Deck Seal Tech Data Sheet for More Info)	
PRODUCT USES	
Stone Edge Surfaces Deck Seal Tint Pack Colors are 8oz of concentrated color that must be mixed with a full 5-gallon bucket of Deck Seal deep base. When an 8oz bottle of Deck Seal Tint Pack color is mixed with our Deck Seal deep base waterproofing sealer, the combined colored Deck Seal is used as the Top Coat Waterproofing layer of the Stone Edge Surfaces Deck and Balcony Waterproofing System, and is also used on Concrete and Concrete Overlay walk decks and balconies, as well as Wood Decks. Application: Stir Deck Seal Well before use. Pour complete contents of 1 - 8oz bottle of Deck Seal Tint Pack Color into 1 - 5 Gallon bucket of Deck Seal deep base Waterproofing Sealer and mix with a mechanical mixer for at least 3 to 5 minutes or until color is uniform throughout with no streaking. Once mixed, Deck Seal is ready for use. APPLICATION: See Deck Seal Application Methods.	
PRODUCT CAUTIONS	
Stone Edge Surfaces Deck Seal Tint Pack Colors are NOT meant to be applied as a standalone product and must be mixed with Stone Edge Surfaces Pro Seal deep base to create a colored or tinted waterproofing sealer. Be careful as Deck Seal Tint Pack colors are concentrated pigment stains and any concrete you or wood you get them on will stain...protect concrete, wood, stucco etc., that you do not wish to color from spills, splashing, leaking, or accidental transfer from disposing of empty bottles. You must mix the Deck Seal base coat and 8oz bottle of Deck Seal Tint Pack colors for as long as it takes until you no longer see streaks of color in the bucket. This could be 3 to 5 minutes or longer in some cases. The mix ratio is 1 – 8oz Bottle of Deck Seal Tint Pack color to 1 – 5 gallon bucket of Deck Seal deep base. To maintain consistent color, always mix full Tint Pack color bottles with full 5 – gallon buckets of Deck Seal. Do Not Mix partial bottles or buckets Do not apply if rain is expected within 48 hours or if temperatures fall below 50 degrees within 24 hours of application.	
PRODUCT PHYSICAL PROPERTIES	
See SDS Sheet for Physical Properties and Safety Information	
PRODUCT BENEFITS	
Easy to use	Soap and water clean up
Convenient 8oz bottle	1:1 ratio of one 8oz bottle to 1 – 5 gallon bucket
PRODUCT CLEANABILITY	
When mixed with Deck Seal deep base, the smoother the finished texture, the easier the surface is to clean, but there is a loss of skid resistant properties. Cleaning and disinfecting compounds and cleaning techniques can affect the color, gloss, texture and performance of the product. It is recommended to clean the surface with water only and possibly a “soft” pressure wash. If using cleaning products or light soapy water, test on a non-conspicuous area before use on entire surface.	
PRODUCT COVERAGE & WEIGHT	
Deck Seal Tint Pack 8oz color bottle, when mixed with Deck Seal deep base, will cover approximately 75-100 sqft per gallon with a Weights of 10.95 lbs per gallon.	
PRODUCT SHELF LIFE	
If properly stored, the expected shelf life can exceed 6 months. However, it is recommended that product be used as soon as possible after delivery. Rotate stock to use oldest inventory first. Store under roof and keep dry.	
PRODUCT LIMITED WARRANTY	
Limited Warranty: Stone Edge Surfaces, a division of Turley International Resources, LLC., (further known as manufacturer), products are warranted to be free of manufacturers defect in material and formulation for 90 days (the warranty period) from the date of purchase from manufacturer, when applied per manufacturer’s instructions, and as provided specifically in the terms and conditions herein. TERMS: Upon verification of factory defect, manufacturer reserve the right, at its sole discretion, to replace the product purchased or refund the purchase price paid to the manufacturer. The refund amount will be based on the most current product pricing at the time warranty coverage is approved. For Products to be deemed warrantable, they must be inspected and warranty approved by an authorized manufacturer representative. This Limited Warranty does not cover, nor is manufacturer responsible for, any project costs or delays, and no remedies will be made for loss and/or usage of fuel, labor, demolition, haul away, clean up, service, travel, transport, reapplication, parts, or any other costs in excess of the purchase price of the products paid to the manufacturer or use of resources resulting from a failure of a warrantable product. Warranty also does not cover products that have been modified, altered, improper mixing not in accordance with manufacturers guidelines or instructions, misused or used in a way not recommended by manufacturer, used after shelf life expiration, acts of God, adverse environmental conditions beyond manufacturers control, inadequate contractor skill level or quality of contractor workmanship, fading over time, improper prep of application area, chemical damage, unstable, cracking or shifting substrate causing product failure. Product replacement or refund of product purchase price from manufacturer are manufacturer’s sole obligations under this limited warranty.	