

PRODUCT AND COMPANY IDENTIFICATION	
PRODUCT MANUFACTURER: Stone Edge Surfaces	MANUFACTURER: Turley International Resources, LLC.
PRODUCT NAME: Pro Seal 2000	4322 South 80 th Street
	Mesa, AZ 85212 - USA
	TEL: 844-786-6333 E: info@stoneedgesurfaces.com
EMERGENCY: Contact Local Hospital or call 911 in US	MEDICAL: Contact Local Hospital or call 911 in US
PRODUCT COMPOSITION	
Stone Edge Surfaces Pro Seal 2000 is a UV resistant, high gloss, 30% solids, Xylene solvent based, acrylic copolymer, curing and sealing compound, as well as a dust-proofer for concrete surfaces. Pro Seal 2000 offers improved resistance to rain, sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to concrete. Pro Seal 2000 forms a superior moisture retentive film on freshly placed concrete.	
PRODUCT USES	
Stone Edge Surfaces Pro Seal 2000 is recommended for both interior and exterior freshly placed, finished, and aged concrete where a high gloss solvent based curing and sealing compound is specified. Pro Seal 2000 can be used on driveways, patios, walkways, porches, interior concrete floors as well as other concrete surfaces where Stone Edge Surfaces Pro Spray, Stamp, Trowel and Micro Coating Mixes have been used. Pro Seal 2000 can be used as a means of dust-proofing most concrete surfaces. Pro Seal 2000 dries to a Glossy finish.	
PRODUCT CAUTIONS	
Pro Seal 2000 will not freeze during storage; however allow temperature to rise to 50 degrees prior to application. All HVAC ventilation ducts should be somehow blocked prior to application so solvents fumes are not distributed. Keep away from open flames. Pro Seal 2000 is flammable and is very susceptible to ignition. It is not recommended to apply Pro Seal 2000 over carpet, tile, or other types of floor adhesives. Pro Seal 2000 was designed as a cure and seal and to be applied in one-two medium coats, not one thick coat. Please be aware that this product when cured may be slippery when wet. Pro Seal 2000 is not resistant to brake fluid, gasoline, and many similar products. It is not recommended to thin Pro Seal 2000. Improper thinning may cause sealer to delaminate in a short time frame. Pro Seal 2000 may darken the surface of many new and existing concrete slabs. Test prior to use. Do not apply if rain is expected within 12 hours or if temperatures fall below 50 degrees within 24 hours of application. Pro Seal 2000 must be applied using proper preparation and installation procedures for the Stone Edge Surfaces warranty to be valid. Substrate temperature must be no less than 40° F., and not exceeding 80° F. If applied outside these limits, the sealer may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing, or hazing. Concrete surface must be clean and free of all contaminants and water. If moisture is present or if the surface is not clean and free of all contaminants, the sealer may have white spots and have premature delamination and failure. May be applied when damp (not "wet") to freshly placed concrete surfaces. Thick or puddle areas may prevent the solvent from evaporating and may be susceptible to moisture intrusion which may cause milky white spots. Applying too thin may cause sealer to prematurely delaminate, flake or wear away. Allow sealer to dry for 24 hours for light traffic and at least 48 hours for heavy traffic. If applying two coats, wait approximately 4 - 6 hours between coats.	
PRODUCT PHYSICAL PROPERTIES	
Best Application Temperature range = 40°F - 85°F	
Meets USDA AASHTO-M-148 DRIED COATING criteria for a Structural Surface that may come in contact with food	
OTC Compliant & Other Relevant Information	Best for Concrete, Masonry, Brick, and Stucco
	Limitations. Above grade use only - vertical surfaces only read label before use
	Dry Time = 1 - 2 hours
	Recoat = 2 - 24 hours
	Wheel Traffic = 24 - 48 Hours
	Foot Traffic = 4 - 6 hours
	Gloss / Sheen = High Gloss
	Solvent Resistance = Minimal
	Concrete Adhesion = Excellent
Solids = 30%	
See SDS Sheet for Physical Properties and Safety Information	
PRODUCT BENEFITS	
Keeps concrete surfaces looking new and clean	Strengthens surface area
High solids content and superior UV protection creates a highly desired finish	Low maintenance cost
Formulated as a very high solids-high gloss sealer, it rolls out smooth with no roller streaks	Excellent dust proofer
Easy to use, high gloss, and low cost makes this a contractor's favorite	Deep penetrating
May be applied with airless sprayer or roller	Non-yellowing
Cure and seal that may be applied to damp yet not wet concrete	
PRODUCT CLEANABILITY	
Overlay products, the smoother the finished texture, the easier the surface is to clean, but there is a loss of skid resistant properties. Cleaning and disinfecting compounds and cleaning techniques can affect the color, gloss, texture and performance of the system. As the precautionary step, Stone Edge Surfaces recommends that the end-user test their cleaning and disinfecting compounds on a non-conspicuous area before use.	
PRODUCT COVERAGE	
Pro Seal 2000 5 Gallon Pail - Approximately 1000 sqft. *Coverage rates vary depending on porosity and texture, and application method. Excessive build up should be avoided.	

TECHNICAL DATA SHEET

PRO Seal 2000

PRODUCT SHELF LIFE

If properly stored, the expected shelf life can exceed 6 months. However, it is recommended that product be used as soon as possible after delivery. Rotate stock to use oldest inventory first. Store under roof and keep dry.

PRODUCT LIMITED WARRANTY

Limited Warranty: Stone Edge Surfaces, a division of Turley International Resources, LLC., (further known as manufacturer), products are warranted to be free of manufacturer's defect in material and formulation for 90 days (the warranty period) from the date of purchase from manufacturer, when applied per manufacturer's instructions, and as provided specifically in the terms and conditions herein. TERMS: Upon verification of factory defect, manufacturer reserve the right, at its sole discretion, to replace the product purchased or refund the purchase price paid to the manufacturer. The refund amount will be based on the most current product pricing at the time warranty coverage is approved. For Products to be deemed warrantable, they must be inspected and warranty approved by an authorized manufacturer representative. This Limited Warranty does not cover, nor is manufacturer responsible for, any project costs or delays, and no remedies will be made for loss and/or usage of fuel, labor, demolition, haul away, clean up, service, travel, transport, reapplication, parts, or any other costs in excess of the purchase price of the products paid to the manufacturer or use of resources resulting from a failure of a warrantable product. Warranty also does not cover products that have been modified, altered, improper mixing not in accordance with manufacturers guidelines or instructions, misused or used in a way not recommended by manufacturer, used after shelf life expiration, acts of God, adverse environmental conditions beyond manufacturers control, inadequate contractor skill level or quality of contractor workmanship, fading over time, improper prep of application area, chemical damage, unstable, cracking or shifting substrate causing product failure. Product replacement or refund of product purchase price from manufacturer are manufacturer's sole obligations under this limited warranty.