

Stone | EDGE

SURFACES

Professional Grade Concrete Overlays



HAIRLINE CRACK FILL MIX (Accent Enhancer) applications



Hairline Crack
BEFORE



Hairline Crack
AFTER

DESCRIPTION

Stone Edge Surfaces Hairline Crack Fill Mix, also known as Accent Enhancer, is a 2-component mix that is combined at a 1:1 ratio with Stone Edge Surfaces Primer 100, and is used on concrete, concrete overlays, decorative concrete and stone veneer to repair hairline cracks. It is also used to “mottle” or accent the colors to add realism during the coloring process. **As a Color or Accent Enhancer:** You apply Accent Enhancer lightly over “just the high spots” of the stamped or carved and sufficiently dried overlay, “before” applying your other colors. Accent Enhancer helps achieve a more realistic varied shaded color or mottled look sporadically throughout the project without having to mix and apply multiple colors of the same hues to achieve the same look.

As a Hairline Crack Fill, Accent Enhancer is mixed as a thicker slurry to fill, fix and repair hairline stress cracks and crazing that may appear as the concrete overlay dries. It is applied into and over the cracks in the same general way you would grout tiles, including wiping away the excess material. To match a finished job, Accent Enhancer can be integrally colored or colored topically. The mix comes in Gray (FXC170) or White (FXC330) in 2.5 Gal. Buckets

MOST COMMON USES

- Hairline Crack Fill (Vertical and Horizontal)
- Color mottling or enhancing (vertical and Horizontal)

APPLICATION

BASE/TOP COAT: Top Coat, applied feather thin before coloring, and into hairline cracks.

APPLICATION METHOD: For hairline cracks use a Cellulose sponge and apply into the crack and wipe away excess...similar to grouting. As a Color Enhancer, use just a small amount on a cellulose sponge and lightly rub just a little on the high spots of the textured surface. Let dry and apply color. Everywhere you applied the mixture will dry lighter and mottle the color and add realism.

WORKING TIME: Average 3 to 5 minutes as it is feather thin in most applications

PRODUCTS USED WITH:

- Primer 100 (1:1 ratio)
- Wall Mix, Stamp Mix, Trowel Mix, Spray Mix,

COMMONLY APPLIED OVER:

- Concrete Surfaces
- Concrete Overlays
- In Hairline Cracks
- Stone Veneer
- Concrete

For additional installation examples, images and training Videos, visit us online, call or email:

www.stoneedgesurfaces.com | 844-786-6333

info@stoneedgesurfaces.com

Stone Edge Surfaces Division - Turley International Resources, LLC 4322 South 80th Street, Mesa, AZ 85212